


PLUMBED-IN FIRE EXTINGUISHER SYSTEMS HOMOLOGATED ACCORDING TO FIA STANDARD 8865-2015

TECHNICAL LIST N° 52

| | | |
|---------------------------|---|--|
| Homologation label |  | In compliance with: FIA Standard 8865-2015 |
| | Manufacturer Name: Name of Manufacturer | |
| | Serial N°: xxx xxx | |
| | Model | : Model Name |
| | Homologation N° | : EX.XXX.XX |
| | Type of Extinguishant | : Extinguishing medium |
| | Range of Temperature | : -15°C to 80°C |
| Class of Fire | : Class I (Petrol in accordance with Art. 9 of | |
| Weight/volume of: | Article 252 of the 2014 Appendix J) | |
| * Complete bottle | : xx kg | |
| * Extinguishant | : yy kg or yy lt | |

| | | |
|--------------------------|---|---|
| Maintenance label |  | Service carried out by: Name - «Name of Manufacturer» |
| | Serial N°: xxx xxx | |
| | Date of Service | : JAN 2019 |
| | Date of Next Service | : JAN 2021 |

Classification of fires:

Class I – Petrol in accordance with Art. 9 of Article 252 of the 2021 Appendix J
 Class II – Petrol + up to 30% ethanol
 Class III – Diesel in accordance with Art. 9 of Article 252 of the 2021 Appendix J
 Class IV – Ethanol up to 100% or methanol up to 100%
 Class V – Any other specific fuel

Label background colours:

Class I – white
 Class II – yellow
 Class III – silver
 Class IV – green
 Class V – turquoise
 An extinguishing medium approved for use on more than one class of fire – gold.

Cockpit volume = cockpit + luggage compartment volume if there is no bulkhead between them. Cockpit volume is the total volume throughout which the extinguishing medium is spread.

[IF YOU CLICK HERE, YOU CAN DOWNLOAD ALL THE PRESENTATION FORMS AND USER MANUALS](#)

Part 1 - Plumbed-In Fire Extinguishers

| HOMOL. NUMBER | BRAND | MODEL | EXTINGUISHING MEDIUM | COCKPIT VOLUME | CLASS OF FIRE | NUMBER OF BOTTLES | START OF HOMOL. | END OF HOMOL. (1) |
|---------------|-------|-------|----------------------|----------------|---------------|-------------------|-----------------|----------------------|
|---------------|-------|-------|----------------------|----------------|---------------|-------------------|-----------------|----------------------|

⁽¹⁾ The homologation end date represents the final date on which the products may be manufactured

⁽²⁾ The validity of the product must always be that which is indicated on the product homologation label. The dates in this column are the latest possible dates that can be shown on the homologation label

| HOMOL. NUMBER | BRAND | MODEL | EXTINGUISHING MEDIUM | COCKPIT VOLUME | CLASS OF FIRE | NUMBER OF BOTTLES | START OF HOMOL. | END OF HOMOL. ⁽¹⁾ |
|---------------|------------|-------------------------|-------------------------------------|----------------------|-----------------------------|-------------------|-----------------|------------------------------|
| EX.001.15 | LIFELINE | ZERO 3620 – 2.3-4.03 M3 | NOVEC 1230 & AR-AFFF+ (ANTI-FREEZE) | FROM 2.39 TO 4.1 M3 | CLASS I, II, III, IV | 2 | 10.2015 | 10.2020 |
| EX.002.15 | SPA DESIGN | RP-D | NOVEC 1230 | FROM 2.3 TO 4.1 M3 | CLASS III | 2 | 10.2015 | 10.2020 |
| EX.003.15 | SPA DESIGN | RP-T | NOVEC 1230 & F-500 | FROM 2.3 TO 4.1 M3 | CLASS I, II, V-E85 | 2 | 10.2015 | 10.2020 |
| EX.004.15 | SPA DESIGN | RP-S | NOVEC 1230 & F-500 ENCAPSULATOR | FROM 2.3 TO 4.1 M3 | CLASS I, II, V-E85 | 2 | 11.2015 | 11.2020 |
| EX.005.15 | LIFELINE | ZERO 3620 – 1.6-2.3 M3 | NOVEC 1230 & AR-AFFF+ (ANTI-FREEZE) | FROM 1.59 TO 2.39 M3 | CLASS I, II, III, IV, V-E85 | 2 | 12.2015 | 12.2020 |
| EX.006.16 | SPA DESIGN | XTREME-500 | NOVEC 1230 & F-500 ENCAPSULATOR | FROM 2.3 TO 4.1 M3 | CLASS I, II, V-E85 | 2 | 10.2016 | 10.2021 |
| EX.007.16 | SPA DESIGN | XTREME-X | NOVEC 1230 | FROM 2.3 TO 4.1 M3 | CLASS I, II, V-E85 | 2 | 10.2016 | 10.2021 |
| EX.008.16 | FEV | FX G-TEC3300R | FX G-TEC FE36 | FROM 2.8 TO 4.1 M3 | CLASS I | 1 | 10.2016 | 10.2021 |
| EX.009.16 | LIFELINE | ZERO 3620 FIRE MARSHAL | NOVEC 1230 & AR-AFFF+ (ANTI-FREEZE) | FROM 2.39 TO 4.1 M3 | CLASS I, II, III, V-E85 | 1 | 12.2016 | 12.2021 |
| EX.010.17 | FEV | FX G-TEC3300R3 | FX G-TEC FE36 | FROM 2.8 TO 4.1 M3 | CLASS I, II, V-E85 | 1 | 03.2017 | 03.2022 |
| EX.011.17 | SPA DESIGN | XTREME-X-1.4-2.3 | NOVEC 1230 | FROM 1.4 TO 2.3 M3 | CLASS I, II, V-E85 | 2 | 03.2017 | 03.2022 |
| EX.012.17 | LIFELINE | ZERO 3620 FIRE MARSHAL | NOVEC 1230 & AR-AFFF+ (ANTI-FREEZE) | FROM 1.6 TO 2.3 M3 | CLASS I, II, III, V-E85 | 1 | 05.2017 | 05.2022 |
| EX.013.17 | FEV | FX G-TEC2400R3 | FX G-TEC FE36 | FROM 1.59 TO 2.34 M3 | CLASS I, II, V-E85 | 1 | 10.2017 | 10.2027 |
| EX.014.17 | OMP | CESAL4L | NOVEC1230 & AFFF | FROM 2.2 TO 4.1 M3 | CLASS I, II, V-E85 | 1 | 12.2017 | 12.2027 |
| EX.015.17 | OMP | CESAL4S | NOVEC1230 & AFFF | FROM 1.2 TO 2.2 M3 | CLASS I, II, V-E85 | 1 | 12.2017 | 12.2027 |
| EX.016.18 | FEV | FX G-TEC2900R3 | FX G-TEC FE36 | FROM 2.25 TO 3.31 M3 | CLASS I, II, V-E85 | 1 | 03.2018 | 03.2028 |
| EX.017.18 | FEV | FX G-TEC2900R | FX G-TEC FE36 | FROM 2.25 TO 3.31 M3 | CLASS I | 1 | 03.2018 | 03.2028 |
| EX.018.18 | LIFELINE | ZERO 275 - 0-4 M3 | MONNEX & COLD FIRE + (ANTI-FREEZE) | FROM 1.4 TO 4.1 M3 | CLASS I, II | 1 | 12.2018 | 12.2028 |
| EX.019.19 | FEV | N-TEC4100R | NOVEC 1230 | FROM 2.3 TO 4.1 M3 | CLASS I | 1 | 05.2019 | 05.2029 |
| | | | | | CLASS II | | 11.2024 | |
| | | | FK5-1-12 | | | | 10.2024 | |
| EX.020.19 | FEV | N-TEC3550R | NOVEC 1230 | FROM 2.0 TO 3.2 M3 | CLASS I | 1 | 06.2019 | 05.2029 |

⁽¹⁾ The homologation end date represents the final date on which the products may be manufactured

⁽²⁾ The validity of the product must always be that which is indicated on the product homologation label. The dates in this column are the latest possible dates that can be shown on the homologation label

| HOMOL. NUMBER | BRAND | MODEL | EXTINGUISHING MEDIUM | COCKPIT VOLUME | CLASS OF FIRE | NUMBER OF BOTTLES | START OF HOMOL. | END OF HOMOL. (1) |
|---------------|----------|------------------------|----------------------|---------------------|-------------------------|-------------------|-----------------|----------------------|
| | | | | | CLASS II | | 11.2024 | |
| | | | FK5-1-12 | | | | 10.2024 | |
| EX.021.19 | FEV | N-TEC2950R | NOVEC 1230 | FROM 1.25 TO 2.3 M3 | CLASS I | 1 | 06.2019 | 05.2029 |
| | | | | | CLASS II | | 11.2024 | |
| | | | FK5-1-12 | | | | 10.2024 | |
| EX.022.19 | OMP | CESAL5L | NOVEC 1230 & AFFF | FROM 2.2 TO 4.1 M3 | CLASS I, II, III, V-E85 | 1 | 10.2019 | 10.2029 |
| EX.023.19 | OMP | CESAL5S | NOVEC 1230 & AFFF | FROM 1.35 TO 2.5 M3 | CLASS I, II, III, V-E85 | 1 | 10.2019 | 10.2029 |
| EX.024.21 | FEV | FX G-TEC2400R3SV | FX G-TEC FE36 | FROM 0.8 TO 1.15 M3 | CLASS I, II, V-E85 | 1 | 03.2021 | 03.2026 |
| EX.025.21 | OMP | CESAL5LE | NOVEC 1230 | FROM 2.2 TO 4.1 M3 | CLASS I | 1 | 07.2021 | 07.2026 |
| EX.026.21 | OMP | CESAL5SE | NOVEC 1230 | FROM 1.35 TO 2.5 M3 | CLASS I | 1 | 07.2021 | 07.2026 |
| EX.027.21 | SPARCO | 014777EXP | FK 5-1-12 | FROM 2.2 TO 4.1 M3 | CLASS I | 1 | 10.2021 | 10.2026 |
| EX.028.21 | SPARCO | 014779EXP | FK 5-1-12 | FROM 1.35 TO 2.3 M3 | CLASS I | 1 | 11.2021 | 11.2026 |
| EX.029.21 | LIFELINE | ZERO EV – 1.7-3.13 M3 | NOVEC 1230 | FROM 1.7 TO 3.13 M3 | CLASS I, II, IV | 1 | 11.2021 | 11.2026 |
| | | | FK5-1-12 | | | | 04.2024 | |
| EX.030.22 | LIFELINE | ZERO EV – 2.2-4.1 M3 | NOVEC 1230 | FROM 2.2 TO 4.1 M3 | CLASS I, II, IV | 1 | 03.2022 | 03.2027 |
| | | | FK5-1-12 | | | | 04.2024 | |
| EX.031.22 | OMP | CESAL4XS | NOVEC1230 & AFFF | FROM 0.6 TO 1.12 M3 | CLASS I, II, V-E85 | 1 | 05.2022 | 05.2027 |
| EX.032.22 | LIFELINE | ZERO EV – 0.96-1.7 M3 | NOVEC 1230 | FROM 0.96 TO 1.7 M3 | CLASS I, II, IV | 1 | 10.2022 | 10.2027 |
| | | | FK5-1-12 | | | | 04.2024 | |
| EX.033.23 | LIFELINE | ZERO 275L – 1.4-4.1 M3 | MONNEX & COLD FIRE | FROM 1.4 TO 4.1 M3 | CLASS V-E75 & E85 | 1 | 09.2023 | 09.2028 |
| EX.034.24 | FEV | CF- TEC2700EK | COLDFIRE | UP TO 4.1 M3 | CLASS I, II, V-E85 | 1 | 05.2024 | 05.2029 |
| EX.035.24 | FEV | CF- TEC2700MK | COLDFIRE | UP TO 4.1 M3 | CLASS I, II, V-E85 | 1 | 10.2024 | 10.2029 |

(1) The homologation end date represents the final date on which the products may be manufactured

(2) The validity of the product must always be that which is indicated on the product homologation label. The dates in this column are the latest possible dates that can be shown on the homologation label

Part 2 - Hand-Held Fire Extinguishers

| HOMOL. NUMBER | BRAND | MODEL | EXTINGUISHING MEDIUM | COCKPIT VOLUME | CLASS OF FIRE | NUMBER OF BOTTLES | START OF HOMOL. | END OF HOMOL. (1) |
|---------------|--------|------------------------|----------------------|----------------|-----------------------------|-------------------|-----------------|----------------------|
| ME.001.24 | FIREXO | 1.4L FIREXO ALL FIRES | FIREXO ALL FIRES | 1.4L | CLASS I, II, III, IV, V-E85 | 1 | 05.2024 | 05.2029 |
| ME.002.24 | FIREXO | 1.75L FIREXO ALL FIRES | FIREXO ALL FIRES | 1.74L | CLASS I, II, III, IV, V-E85 | 1 | 05.2024 | 05.2029 |
| ME.003.24 | FIREXO | 2.0L FIREXO ALL FIRES | FIREXO ALL FIRES | 2.0L | CLASS I, II, III, IV, V-E85 | 1 | 05.2024 | 05.2029 |
| ME.004.24 | FIREXO | 2.4L FIREXO ALL FIRES | FIREXO ALL FIRES | 2.4L | CLASS I, II, III, IV, V-E85 | 1 | 05.2024 | 05.2029 |
| ME.005.24 | FIREXO | 6.0L FIREXO ALL FIRES | FIREXO ALL FIRES | 6.0L | CLASS I, II, III, IV, V-E85 | 1 | 05.2024 | 05.2029 |
| ME.006.24 | FIREXO | 9.0L FIREXO ALL FIRES | FIREXO ALL FIRES | 9.0L | CLASS I, II, III, IV, V-E85 | 1 | 05.2024 | 05.2029 |

⁽¹⁾ The homologation end date represents the final date on which the products may be manufactured

⁽²⁾ The validity of the product must always be that which is indicated on the product homologation label. The dates in this column are the latest possible dates that can be shown on the homologation label

HOMOLOGATIONS OF PLUMBED-IN FIRE EXTINGUISHER SYSTEMS / WARNING

There are no warnings for this product

⁽¹⁾ The homologation end date represents the final date on which the products may be manufactured

⁽²⁾ The validity of the product must always be that which is indicated on the product homologation label. The dates in this column are the latest possible dates that can be shown on the homologation label